

# HDX-4KNVR832-P

32 Channel, 16 PoE Ports, H.265 / H.264 Video Compression,  
4K UltraHD Recording Resolution Network Video Recorder

## Technical Specifications



- 32 IP Channel Inputs
- 16 Independent 10/100M PoE Ports
- H.265 / H.264 Video Compression
- Up to 8MP Recording Resolution
- 1 HDMI (Up to 4K Resolution) and 1 VGA Video Outputs
- 8 SATA Interfaces for Internal Storage up to 6TB each, 1 eSATA Interface
- 1 RJ-45 10/100/1000M Ethernet Interface
- Supports NAT functionality and QRCode scanning for mobile device access
- ONVIF Compliant

| HDX-4KNVR832-P         |                                                        |
|------------------------|--------------------------------------------------------|
| IP Camera Inputs       | 32 Channels                                            |
| Video Output Interface | 1 HDMI, 1 VGA                                          |
| Display Resolution     | HDMI: 4K (3840 x 2160); 1920 x 1080; 1280 x 1024       |
|                        | VGA: 1920 x 1080; 1280 x 1024                          |
| Audio Output Interface | 1 Channel, RCA Audio Output                            |
| Two-way Audio          | 1 Channel, RCA Audio Input                             |
| Recording Resolution   | 8MP / 5MP / 4MP / 3MP / 1080p / 960p / 720p            |
| Recording Bandwidth    | 256Mbps                                                |
| Simultaneous Playback  | Maximum 16 channels                                    |
| Alarm Inputs           | 16 Channels                                            |
| Relay Outputs          | 4 Channels                                             |
| Network interface      | 1 x 10/100/1000M RJ-45 Ethernet Interface              |
| PoE Ports              | 16 x 10/100M RJ-45 PoE Ports                           |
| Remote Connections     | 10 Remote Users Maximum                                |
| HDD Interfaces         | 8 SATA Interfaces, maximum 6TB each, 1 eSATA Interface |
| Backup Media           | External USB or Network Download                       |
| USB Interfaces         | 1 x USB2.0 (Front), 1 USB3.0 (Rear)                    |
| Power Supply           | Internal ATX Power Supply                              |
| Power Consumption      | < 15W (Without HDD)                                    |
| Operating Environment  | 14" - 122°F, less than 90% Relative Humidity           |
| Dimensions             | 16.9" x 17.7" x 3.5"                                   |
| Weight (without HDD)   | ~24lbs                                                 |

