

32 Channel, High Definition 5-in-1 Digital Video Recorder



- 32 BNC Video Inputs Supporting AHD, TVI, CVI and CVBS
- Supports 4 IP Cameras up to 5MP Resolution
- H.264 Video Compression
- Up to 1080p Recording Resolution
- 1 HDMI, 1 VGA and 1 CVBS BNC Video Output
- 8 SATA Interfaces for Internal Storage up to 8TB per HDD
- 1 RJ-45 10/100/1000M Ethernet Interface
- Supports NAT functionality and QRCode scanning for mobile device access

Technical Specifications

HDX-XVR832	
Video Input Interface	32 BNC Video Inputs
Video Input Signal	AHD, TVI, CVI, CVBS
IP Input Bandwidth	4 IP Cameras @ 24Mbps
Video Output Interface	1 HDMI, 1 VGA, 1 CVBS (BNC)
Display Resolution	1920 x 1080; 1280 x 1024
Audio Input Interface	16 Channel, RCA Audio Inputs
Audio Output Interface	1 Channel, RCA Audio Output
Two-way Audio	1 Channel, RCA Audio Input (Uses Channel 1 Audio Input)
Recording Resolution	1080p, 1080p lite, 720p WD1
Frame Rate	1080p: 15fps (NTSC) / 1080p lite, 720p, WD1: 30fps (NTSC)
Bit Rate	768Kbps - 8Mbps
IP Recording Rate	5MP@15fps; 4MP@20fps; 3MP / 1080p / 960p / 720p@30fps
Simultaneous Playback	Maximum 16 channels
Alarm Inputs	16 Channels
Relay Outputs	4 Channels
Network interface	1 x 10/100/1000M RJ-45 Ethernet Interface
Remote Connections	10 Remote Users Maximum
HDD Interfaces	8 SATA interfaces, maximum 8TB per HDD
Backup Media	External USB or Network Download
USB Interfaces	1 x USB2.0 (Front), 1 USB3.0 (Rear)
RS-485 Interface	2 Ports for Serial PTZ Control
Power Supply	250W ATX Internal Power Supply
Power Consumption	< 40W (Without HDD)
Operating Environment	14" - 122°F, less than 90% Relative Humidity
Dimensions	16.9" x 17.7" x 3.5"
Weight (without HDD)	~22lbs

